

The Best Source for External Storage Solution

SMART STORAGE ENCLOSURE FOR 3.5" & 5.25" DRIVES

TT-345 Series



Description:

The TT-345 Series Enclosure is designed for any 3.5" & 5.25" IDE storage drives, such as 3.5" Hard Drives, Tape Back-Up, Zip Drives, and 5.25" CD, CD-RW, DVD, DVD+RW drives. This series provide unlimited storage expansion with the most flexibility.

Features:

Light, Stylish and professionally designed
Easy for Installation of Drives

UL/CSA/TUV CE/FCC Class B certified
(L x W x H) = (9.6" x 6.5" x 2.15")

Power Supply Specifications:

Input Voltage : 110- 240Vac Auto-Switching DC Output : 5V/2.2A 12V/1.5A
Current : 0.6A at 100Vac Maximum
 0.3A at 240Vac Maximum Line Regulation: +/- 1%
Frequency : 50/60 Hz Voltage Regulation: +/- 5%
Efficiency : 75% (Minimum) at Full Load, 110Vac hold up time: 10msec at 115Vac

Environmental:

Operating Temperature : 0°C -40°C Storage Temperature : -10°C -70°C
MTBF : 20,000 Hours (minimum) at full load
Interface Support : IEEE1394 FireWire, USB1.1 & USB2.0

Protection:

Over voltage protection : +5V Clamp at 6.0V (Maximum)
Short Circuit protection : All output (Auto Recovery)

Model No.	Description
-----------	-------------

TT-345F	For 3.5"/5.25" FireWire Hard Drive, CD-R, CD-R/RW/DVD/DVD COMBO
TT-345U2	For 3.5"/5.25" USB2.0 Hard Drive, CD-R, CD-R/RW/DVD/DVD COMBO
TT-345U2F	For 3.5"/5.25" Combo <u>USB2.0</u> & <u>FireWire</u> Drives.



All Trademarks or Registered Trademarks are Property of Their Respective Owners.